

Anti-Fatigue Logo Mats

Specifications

General Information:

Surface

TYPE: 100% Nitrile Rubber (20% Recycled Content)

TENSIL STRENGTH: 1600

THICKNESS: 1/8"

DESIGN: Diamond Wave

DUROMETER: 65

Cushion

CUSHION TYPE: Nitrile Rubber / PVC

CUSHION THICKNESS: 0.5"

CUSHION DENSITY: 5lbs/ft

Features:

1. U.V. stable, solid nitrile rubber top surface for excellent chemical resistance
2. Textured nitrile rubber surface for superior slip resistance
3. ASTM C1028-96 Static Coefficient of Friction: Dry = 0.92 Wet = 0.86
4. Closed-cell Nitrile / PVC cushion backing provides long lasting comfort
5. Nitrile Rubber border remains flexible for the life of the mat and will not crack or curl
6. Available in 24", 33", and 46" widths up to 40" length
7. Crush-resistant, molded rubber surface pattern provides traction even under wet conditions while maintaining high performance and extending product life.
8. Lays flat, won't crack or curl like vinyl mats. Certified by the National Floor Safety Institute (NFSI) and is ADA-compliant.
9. Cushion is permanently bonded to the Nitrile rubber top surface layer and will not delaminate like mats with a glued cushion.
10. Easy to clean: Just sweep, shake out or wipe with a slightly moist mop or rag.
11. Use in retail stores, point-of-sale areas, kiosks, concierge desks, trade shows and front desks.
12. Passes Flammability Standard DOC-FF-1-70
13. Passes ATTCC Test Method 134-1996 Electrostatic Propensity of Carpets: Maximum Voltage Negative 0.7 KV
14. Static Decay Test Method 4045 Federal Standard 101B/NFPA 99 12-4.1.3.8 (F)(3)(I) – Maximum Time Recorder: 0.91 sec
15. Anti-Static ANSI/ESD 57-1 1994 Protection of Electrostatic Discharge of Susceptible items: Flooring Materials.