

Carpet Entrance Mats

Specifications

General Information:

Surface

Fiber Type:	Tufted Olefin
Weight:	16 ozs/sqyd
Carpet Height:	1/4"
Design:	Cut-Pile

Backing

Type:	100% PVC Vinyl
Thickness:	1/8" – Border; 3/8" Total Thickness
Durometer:	60

General

Overall Thickness:	3/8"
Overall Weight:	0.73 lbs/sqft

Features:

- Olefin surface material is constructed to resist crushing, maintain high performance and extend overall product life.
- Border is designed to hold water and dirt on mat keeping them off carpets and floors.
- Olefin surface removes and traps dirt and moisture and holds it on mat below shoe level so it is not tracked in.
- Vinyl backing minimizes movement and improves traction on hard surfaces.
- Durable anti-static Olefin face suitable for indoor or outdoor use.
- Olefin fiber system dries quickly preventing fading and rotting. Material is stain and mildew resistant.
- Easy to clean: Just vacuum or hose off and hang to dry.
- Not adversely effected by salt or ice melt.
- Should not be used in areas exposed to animal fats (kitchens) or petroleum products.
- Passes Flammability Standard DOC-FF-1-70
- Anti-static: Carpet Entrance Mats have a maximum average voltage of 1.6 KV as measured by the AATCC 134 Electrostatic Propensity Test and meets IBM's minimum standard for electrical resistance (NFPA99).
- ASTM C 1028-89 Static Coefficient of Friction Dry 0.65