

Complete Comfort Launderable Anti-Fatigue Mats

Specifications

General Information:

Uniform Construction

TYPE: 100% Closed-Cell Nitricell (Nitrile Rubber/PVC foam)

TENSIL STRENGTH: 1525

THICKNESS: 5/8"

DENSITY: 4.5lbs/ft

DUROMETER: 60

Features:

1. U.V. Stable (both versions: with and without holes)
2. Nitricell foam does not absorb liquids and offers superb chemical resistance against greases and oils.
3. Multi-directional, textured surface for excellent slip resistance
4. ASTM C1028-96 Static Coefficient of Friction: Dry = 0.80 Wet = 0.70
5. Closed-cell Nitricell cushioned construction provides long lasting comfort
6. Uniform Nitricell construction remains flexible for the life of the mat and helps prevent cracking and curling
7. Available in 24", 33", and 46" widths up to 75' length
8. Uniform construction ensures material will not delaminate
9. Passes Flammability Standard DOC-FF-1-70
10. Passes ATTCC Test Method 134-1996 Electrostatic Propensity of Carpets: Maximum Voltage Negative 0.7 KV
11. Static Decay Test Method 4045 Federal Standard 101B/NFPA 99 12-4.1.3.8 (F)(3)(I) – Maximum Time Recorder: .91 sec
12. Anti-Static ANSI/ESD 57-1 1994 Protection of Electrostatic Discharge of Susceptible items: Flooring Materials