



Tire Tile

Recycled Rubber Modular Tile
 Available 12" x 12"
 25 per case - Thickness 3/8"

PRODUCT SPECIFICATIONS

PRODUCT COMPOSITION	STANDARD/NORMS	DATA
Manufacturing Process:		Selected bus and truck tires
Surface Aspect:		Buffed, chenille-like fluff cord
Product composition		Recycled Rubber Tire Strips
Primary Backing		Non-flammable solid adhesive base
PRODUCT DIMENSIONS		
Thickness		3/8" (with a tolerance + 1/8" - 0")
Total Weight		2 lbs/sqft
Total Size		12" x 12"
FLAMMABILITY RATING		
Complies with the Consumer Products Safety Commission Regulations	DOC-FF-1-70 & AMBIC Test	Exceeds the minimum char radius of 3" Average char, per 8 strips tested, .75" radius
TIRE TILE ADHESIVE		
Base	Urethane	
Viscosity	70,000 CPS	
Color	Black	
Shelf Life	1 year in a closed container	
Coverage	Approx. 75 - 100 sqft per gallon	

INSTALLATION

Floor area should be completely clean, dry, and free of foreign substances. Use a floor leveler as needed to ensure floor is smooth, even and without cracks. Our matting products can be cut easily to any size, shape or pattern with a utility knife. Follow adhesive manufacture's instructions.

Adhesive: Tire Tile Adhesive or approved equal.

CLEANING & MAINTENANCE

Daily: Vacuum daily with a commercial grade vacuum cleaner that features a rotary power brush or beater bar. Mats release more soil when completely dry.

Periodic Maintenance: Our matting products clean beautifully with the use of a Hot Water Extraction machine. Minimum quarterly intervals recommended for high traffic applications. For optimum performance during winter months, traffic lanes may require more frequent extraction cleaning depending on weather conditions and climate.

WARRANTY

Limited 3-Year Abrasive Warranty. limited warranty for abrasive wear on indoor installations. Warranty requires product installation over a dry, smooth, hard, flat surface free of cracks and foreign substances. Product damage from unusual abuse is not covered. Product must be installed using the appropriate brand adhesive, or approved equal. Product must be maintained according to maintenance instructions. Adjustment under this warranty will be on a pro-rated life basis and will cover the shipped material from date of receipt at the jobsite.