

# Super Berber Matting

Heavy duty multi-directional Nop pattern; Ideal for high traffic areas (Rubber backed)  
 Available in 6'7" & 13'2" roll widths

## PRODUCT SPECIFICATIONS

| PRODUCT COMPOSITION              | STANDARD/NORMS                       | DATA                                                  |
|----------------------------------|--------------------------------------|-------------------------------------------------------|
| Manufacturing process            | ISO 2424                             | Needle punched                                        |
| Pile Yarn Composition            | CEE 83/623                           | 100% solution-dyed UV stabilized polypropylene fibers |
| Primary Backing                  | ISO 2424                             | High density rubber                                   |
| <b>PRODUCT DIMENSIONS</b>        |                                      |                                                       |
| Pile Height (+ or - 0.5mm)       | ISO 1766                             | .20 inches                                            |
| Total Height (+ or - 7.5%)       | ISO 1766                             | .43 inches                                            |
| Pile Weight (+ or - 7.5%)        | ISO 8543                             | 42.8 oz/yd                                            |
| Total Weight (+ or - 7.5%)       | ISO 8543                             | 73.1 oz/yd                                            |
| <b>ELECTROSTATIC PROPERTIES</b>  |                                      |                                                       |
| Dimension Stability              | EN 986                               | Pass                                                  |
| Walk On Test                     | ISO TR 6356                          | < 2 KV                                                |
| <b>COLOR FASTNESS</b>            |                                      |                                                       |
| To Light                         | ISO 105 B02                          | >=6                                                   |
| To Water                         | ISO 105 E01                          | 5                                                     |
| To Shampoo                       | BS 1006 UK-TB                        | 5                                                     |
| To Rubbing (dry & wet)           | ISO 105 x 12                         | 4-5                                                   |
| <b>FLAMMABILITY RATING</b>       |                                      |                                                       |
| Pill test (Surface flammability) | ISO 6925 / ASTM D2859 / CPSC FF 1-70 | Passes Federal Flammability Standard                  |

## INSTALLATION

Floor area should be completely clean, dry and free of foreign substances. Use a floor leveler as needed to ensure floor is smooth, even and without cracks. Our matting products can be cut easily to any size, shape or pattern with a utility knife. In glue-down applications, follow adhesive manufacturer's instructions.

**Adhesive (if applicable):** Multi-Bond Mat Adhesive, or approved equal.

## CLEANING & MAINTENANCE

**Daily:** Vacuum daily with a commercial grade vacuum cleaner that features a rotary power brush or beater bar. Mats release more soil when completely dry.

**Periodic Maintenance:** Our matting products clean beautifully with the use of a Hot Water Extraction machine. Minimum quarterly intervals recommended for high traffic applications.

For optimum performance during winter months, traffic lanes may require more frequent extraction cleaning depending on weather conditions and climate.

## WARRANTY

**Limited 3-Year Abrasive Warranty.** limited warranty for abrasive wear on indoor installations. Warranty requires product installation over a dry, smooth, hard, flat surface free of cracks and foreign substances. Product must be installed using the appropriate adhesive, or approved equal. Product must be maintained according to maintenance instructions.