

# SuperScrape Plus Rubber Mats

## Specifications

### General Information:

Type:	100% Nitrile Rubber (20% Recycled Content)
Weight:	26 ozs/sqyd
Overall Height:	1/4"
Design:	Multi-Directional Scraper Bars
Durometer:	60

### Features:

- Molded rubber surface pattern provides traction even under wet conditions and scrapes heavy soil, dirt and debris from shoe soles. Multi-directional nubs resist crushing, maintaining high performance and extending product life.
- Border is designed to allow water and dirt flow off of the mat keeping the walking surface cleaner, drier and safer.
- ADA-compliant (and also certified by the National Floor Safety Institute).
- Borders can be cut off without degradation to mat.
- Raised NUB surface: Removes and traps dirt and debris and holds particles between nubs of mat, below shoe level, so as not to be tracked in.
- 100% Rubber construction: Lays flat, won't crack or curl like vinyl mats.
- Indoor/Outdoor: Durable anti-static material suitable for indoor or outdoor use.
- Premium, commercial-grade Nitrile rubber dries quickly preventing fading and rotting; UV stable.
- Easy to clean: Just sweep, shake out or hose off and hang to dry.
- Not adversely effected by salt or ice melt.
- Use in kitchens, locker rooms, restaurants, outside entrances, and grocery store produce areas.
- Passes Flammability Standard DOC-FF-1-70
- Anti-Static: Surface to Ground: 4.3 x 10<sup>5</sup> ohms @ 50% Relative Humidity and 4.6 x 10<sup>5</sup> ohms @ 12% Relative Humidity. Surface to Surface: 1.8 x 10<sup>6</sup> ohms @ 50% Relative Humidity and 1.8 x 10<sup>6</sup> ohms @ 12% Relative Humidity. Static Decay Test Method 4046 Federal Standard 101B/NFPA 99 Chapter 12 Section 4.1.3.8 (f)(3)(i) with Maximum Time Recorder at .01 seconds.
- ASTM C 1028-96 Static Coefficient of Friction Dry 0.74.